

# Glue it, Screw it, & Seal it with Grabber

## GSCSF - Professional Strength Acoustical Sound & Smoke Sealant

Non-flammable, water-based product developed specifically for the reduction of sound and smoke transmission in all types of wall partition systems. Easy application and easy cleanup. Used correctly and as directed, sealant will achieve and maintain specific STC (Sound Transmission Class) values specified for various wall system designs. This product should be used in office buildings, sound studios, hospitals, schools, hotels and motels, apartment complexes, and other areas where sound smoke ratings are required. This sealant is also ideal for sealing out air infiltration and unwanted moisture in residential construction.

- ▶ Improves STC Values and upgrades sound quality
- ▶ UL 723 classified
- ▶ Exceeds ASTM C834
- ▶ Test in accordance with ASTM E84, ASTM E90 and ASTM C919
- ▶ Meets NFPA Class A fire rating
- ▶ Smoke sealant



## GSCSF - Green Products LEED Information

Surface Burning  
Characteristics  
For Building materials

Flame	Smoke
0.0	0.0
0.0	0.0

Tested as applied in two 1/4" diameter beads, 8 in. O.C.  
(Coverage: 2.8 percent of the exposed test sample area).

### Product Features

Exceeds the requirements of ASTM C834. Tested in accordance with ASTM E84, ASTM E90 and ASTM C919. Meets NFPA Class A fire rating.

- Environmentally safe – VOC-compliant
- Eliminates sound transmission and seals air gaps
- Improves STC Values and upgrades sound quality
- UL 723 classified
- Repairs cracks and eliminates rattles in drywall and plaster
- Mold and mildew resistant
- Easily tools with one pass
- Cleans easily with water in wet state
- Post-consumer recycled cartridge and carton

- LEED EQ Credit 4.1: Low-Emitting-material, Adhesives and Sealants.
- SCAQMD Rule 1168 Compliant
- Meets GS-36 requirements

**All tubes are 28 oz. (828 ml) cartridges, 12 per case**

**GDWAV****Professional Strength Drywall Adhesive****ADVANCED SOLVENT VOC COMPLIANT**

Grabber Professional Drywall Adhesive is a high-performance, VOC-compliant formula specifically designed for installing drywall and paneling to most common building materials, including wood and metal. It offers excellent adhesion, reduces nail pops and provides a "no sag" installation.

Grabber Drywall Adhesive fills gaps in substrates, providing a more solid backup surface and reducing sound transmission. It is unaffected by moisture and resists aging - it will not become hard or brittle with age.

**Exceeds the requirements of ASTM C557 and has been tested in accordance with E72 for racking and shearing.**

**Product Features**

- ▶ VOC-compliant
- ▶ Strong, fast grab
- ▶ Eliminates nail pops
- ▶ Moisture-resistant
- ▶ Reduces sound transmission
- ▶ Wood & metal studs

**GDWAW****Professional Strength Drywall Adhesive****WATER BASED VOC COMPLIANT**

Grabber Green Products Professional Drywall Adhesive is specifically designed for installing drywall and paneling to most common building materials. It offers excellent adhesion, reduces nail pops and provides a "no sag" installation.

Grabber Green Products Professional Drywall is a VOC-compliant formula containing no ozone depleting chemicals, making it safer for you and the environment. Unlike solvent-based adhesives, it is nonflammable, emits no harmful fumes and cleans up with water.

**Exceeds the performance requirements of the ASTM C557 Specification. Tested in accordance with E72 for racking and shearing.**

**PRODUCT FEATURES**

- ▶ Environmentally safe - VOC-compliant
- ▶ Bonds drywall to wood, metal studs, plaster, wallboard, plywood, paneling and tileboard
- ▶ Excellent strength
- ▶ "No sag" installation
- ▶ Reduces nail pops
- ▶ Cleans easily with water in wet state
- ▶ Cartridge and carton contain post-consumer recycled material

**GSFAV****Weatherproof Subfloor Adhesive****ADVANCED SOLVENT VOC COMPLIANT**

Grabber Professional Weatherproof Subfloor Adhesive is a high-performance, VOC-compliant formula ideal for subfloor installations and general plywood use. It offers a strong initial tack and excellent bond strength for particleboard, OSB, engineered lumber and wet, frozen and treated lumber.

Subfloor Adhesive provides a permanent bond that remains flexible, reduces nailing and eliminates squeaky floors. It can be easily extruded from 0°F - 100°F for applications in various climates.

**Exceeds the requirements of APA's AFG-01, ASTM D3498 and ASTM C557.**

**PRODUCT FEATURES**

- ▶ VOC-compliant
- ▶ Wet & frozen lumber
- ▶ Bridges gaps
- ▶ Eliminates squeaks
- ▶ Reduces nailing
- ▶ Strong, fast grab

**GSFAW****Weatherproof Subfloor Adhesive****WATER BASED VOC COMPLIANT**

Grabber Green Products Weatherproof Subfloor Adhesive is a professional-strength formula designed for subfloor installations and plywood use. It provides a permanent bond that remains flexible, reduces nailing and helps eliminate squeaky floors.

Grabber Subfloor is a VOC-compliant formula containing no ozone depleting chemicals, making it safer for you and the environment. Unlike solvent-based adhesives, it is nonflammable, emits no harmful fumes and cleans up with water.

**Exceeds the requirements of the APA's AFG-01 specification and ASTM C557.**

**PRODUCT FEATURES**

- ▶ Environmentally safe - VOC-compliant
- ▶ Fills gaps and irregularities
- ▶ Reduces the amount of nailing
- ▶ Highly water-resistant when dry
- ▶ Excellent aging qualities
- ▶ Ideal for use on wet, frozen, treated and engineered lumber
- ▶ Offers freeze/thaw stability
- ▶ Cleans easily with water in wet state

