

# **Safety Data Sheet**

## **GREENchoice Subfloor Adhesive**

# **Section 1.Identification**

GHS product identifier : GREENchoice Subfloor Adhesive

Product type : Liquid.
CAS # : mixture

Address : Franklin International

2020 Bruck Street Columbus OH 43207

Contact person : Franklin Technical Services

**Telephone** : (800) 877-4583 **In case of emergency** : Franklin Security (614) 445-1300

Reference number : 3635 Product code : 4122

 Date of revision
 : 12/21/2015.

 Print date
 : 12/21/2015.

 Chemtrec (24 Hour)
 : (800) 424 - 9300

 Chemtrec International
 : (703) 527 - 3887

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

## Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys) (oral) - substance or mixture : Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 17.6%

GHS label elements
Hazard pictograms

and label elements



Signal word : Warning

**Hazard statements** : May cause damage to organs through prolonged or repeated exposure if swallowed.

(kidneys)

**Precautionary statements** 

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

**Prevention** : Do not breathe vapor.

**Response** : Get medical attention if you feelunwell.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

 Date of issue/Date of revision
 : 12/21/2015.

 Version : 4.2
 1/11

# Section 2. Hazards identification

Hazards not otherwise

: None known.

classified

# Section 3. Composition/information on ingredients

# **Hazardous ingredients**

#### **United States**

Name	CAS number	%
10,744	56-81-5 107-21-1	1 - 5 0.5 - 1

#### Canada

Name	CAS number	%
' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	27138-31-4 56-81-5	5 - 10
glycerol ethanediol	107-21-1	1 - 5 0.5 - 1

<u>Mexico</u>				Classification				
Name	CAS number	UN number	%	IDLH	Н	F	R	Special
glycerol	56-81-5	Not available.	1 - 5	-	1	1	0	-
oxydipropyl dibenzoate	27138-31-4	Not available.	5 - 10	-	2	0	0	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

### **Description of necessary first aid measures**

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person.

 Date of issue/Date of revision
 : 12/21/2015.

 Version : 4.2
 2/11

## Section 4. First aid measures

If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact
 Inhalation
 Skin contact
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested orinhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

# See toxicological information (Section 11)

# Section 5. Fire-fighting measures

## Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

ι • ⊏:

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

 Date of issue/Date of revision
 : 12/21/2015.
 Version : 4.2
 3/11

### Section 6. Accidental release measures

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 10 to 32.222°C (50 to 90°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### Control parameters

# **United States**

## Occupational exposure limits

Ingredient name	Exposure limits	
glycerol	OSHA PEL 1989 (United States, 3/1989).  TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 10 mg/m³ 8 hours. Form: Total dust  OSHA PEL (United States, 2/2013).  TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust  OSHA PEL 1989 (United States, 3/1989).  CEIL: 50 ppm  CEIL: 125 mg/m³  ACGIH TLV (United States, 3/2015).  C: 100 mg/m³ Form: Aerosol	

Date of issue/Date of revision : 12/21/2015. Version: 4.2 4/11

# Section 8. Exposure controls/personal protection

#### Canada

Occupational exposure limits		TWA	(8 hours	)	STEL (15 mins)		s)	Ceiling			
Ingredient	List name	ppm	mg/ m³	Other	ppm	mg/ m³	Other	ppm	mg/ m³	Other	Notations
ethanediol	US ACGIH 3/2015	-	-	_	-	_	-	-	100	-	[a]
	AB 4/2009	-	-	-	-	-	-	-	100	-	[3] [b]
	BC 2/2015	-	-	-	-	-	-	-	100	-	[a]
		-	10	-	-	20	-	-	-	-	[c]
		-	-	-	-	-	-	50	-	-	[c] [d]
	ON 7/2015	-	-	-	-	-	-	-	100	-	[b]
	QC 1/2014	-	-	-	50	127	-	-	-	-	[e]
glycerol	AB 4/2009	-	10	-	-	-	-	-	-	-	[3] [f]
	BC 2/2015	-	10	-	-	-	-	-	-	-	[f]
		-	3	-	-	-	-	-	-	-	[g]
	QC 1/2014	-	10	-	-	-	-	-	-	-	[h]

[3]Skin sensitization

Form: [a]Aerosol [b]aerosol [c]Particulate [d]Vapour [e]vapour and mist [f]Mist [g]Respirable mist [h]mist

#### **Mexico**

#### Occupational exposure limits

Ingredient	Exposure limits
glycerol	NOM-010-STPS (Mexico, 9/2000).  LMPE-PPT: 10 mg/m³ 8 hours. Form: mist

Consult local authorities for acceptable exposure limits.

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **Individual protection measures**

## Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

#### Skin protection

#### Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

 Date of issue/Date of revision
 : 12/21/2015.
 Version : 4.2
 5/11

# Section 8. Exposure controls/personal protection

**Body protection**: Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

**Respiratory protection**: Use a properly fitted, air-purifying or air-fed respirator complying with an approved

standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

# Section 9. Physical and chemical properties

#### **Appearance**

Physical state : Liquid. [Paste.]

Color : Off-white.

Odor : Characteristic.
Odor threshold : Not available.

pH : 6.5 to 8.5

Melting point : Not available.

Boiling point : 100°C (212°F)

Flash point : Closed cup: >93.333°C (>200°F) [Setaflash.]

**Evaporation rate** : <1 (butyl acetate = 1)

VOC (less water, less

exempt solvents)

: 49.39 g/l

Relative density : 1.26417

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

**Possibility of hazardous**: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition products should

**products** not be produced.

# Section 11. Toxicological information

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
glycerol	LD50 Dermal	Rabbit	>18700 mg/kg	-
	LD50 Oral	Rat	12600 mg/kg	-
ethanediol	LC50 Inhalation Vapor	Rat	10.92 mg/l	4 hours
	LD50 Oral	Rat	4700 mg/kg	-

Conclusion/Summary

: Not available.

Irritation/Corrosion

 Date of issue/Date of revision
 : 12/21/2015.
 Version : 4.2
 6/11

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
glycerol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
Skin - Mild irritant	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
ethanediol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
Eyes - Mild irritant	Eyes - Mild irritant	Rabbit	-	1 hours 100 milligrams	-
Eyes - Moderate irritant	Eyes - Moderate irritant	Rabbit	-	6 hours 1440 milligrams	-
Skin - Mild irritant	Skin - Mild irritant	Rabbit	-	555 milligrams	-

## Conclusion/Summary

**Skin** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

**Eyes**: This product may irritate eyes upon contact.

**Respiratory**: Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
ethanediol	Category 2 Category 3		kidneys Narcotic effects

Information on the likely routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

## Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

## Delayed and immediate effects and also chronic effects from short and long term exposure

# Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Date of issue/Date of revision : 12/21/2015. Version : 4.2 7/11

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
glycerol	Acute EC50 77712 mg/l	Algae	96 hours
	Acute EC50 1851 mg/l	Crustaceans	48 hours
	Acute LC50 51 mg/l	Fish - rainbow trout	96 hours
ethanediol	Acute EC50 10940 mg/l	Algae - Selenastrum capriocornutum	96 hours
	Acute LC50 13140000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia	48 hours
	Acute LC50 41000000 μg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 8050000 μg/l Fresh water Chronic NOEC 10000 mg/l	Fish - Pimephales promelas Algae - Selenastrum capriocornutum	96 hours 96 hours

#### **Conclusion/Summary**

: Not available.

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
glycerol	-	-	Readily
ethanediol	-	-	Readily

#### **Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
glycerol	-1.76	3.162	low
ethanediol	-1.36	10	low

#### Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

## **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-	-

 Date of issue/Date of revision
 : 12/21/2015.
 Version : 4.2
 8/11

GREENchoice Subfloor Adhesive Section 14. Transport information Packing group **Environmental** No. No. No. No. No. No. hazards Additional

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to Annex II of MARPOL 73/78 and the IBC Code

information

# Section 15. Regulatory information

U.S. Federal regulations : TSCA 8(a) PAIR: methyl acetate; Nonylphenol, branched, ethoxylated

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

**United States inventory (TSCA** All components are listed or exempted.

8b):

Commerce control list precursor: 2-diethylaminoethanol

Clean Air Act Section 112

(b) Hazardous Air

: Not listed

Pollutants (HAPs)

Clean Air Act Section 602 Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances

#### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

SARA 311/312

Classification : Delayed (chronic) health hazard

## Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
glycerol ethanediol		No. No.		No. No.	Yes. Yes.	No. Yes.

## State regulations

Massachusetts : The following components are listed: GLYCERINE MIST

**New York** : None of the components are listed.

**New Jersey** : The following components are listed: GLYCERIN; 1,2,3-PROPANETRIOL

Pennsylvania : The following components are listed: 1,2,3-PROPANETRIOL \_\_\_

California Prop. 65

Date of issue/Date of revision : 12/21/2015. Version: 4.2 9/11

# Section 15. Regulatory information

**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
methanol	No.		(ingestion) 47000 µg/day	23000 µg/day (ingestion) 47000 µg/day (inhalation)

#### Canada

## Canadian lists

Canadian NPRI : None of the components are listed.

CEPA Toxic substances : None of the components are listed.

Canada inventory : Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

#### **Mexico**

Classification :



#### International regulations

International lists : Australia inventory (AICS): Not determined.

China inventory (IECSC): Not determined.

**Japan inventory**: Not determined. **Korea inventory**: Not determined.

Malaysia Inventory (EHS Register): Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined. Taiwan inventory (CSNN): Not determined.

**Europe**: Not determined.

Chemical Weapons

**Convention List Schedule** 

**I Chemicals** 

Chemical Weapons

**Convention List Schedule** 

**II Chemicals** 

Chemical Weapons

**Convention List Schedule** 

III Chemicals

: Not listed

: Not listed

: Not listed

# Section 16. Other information

## **Hazardous Material Information System (U.S.A.)**



 Date of issue/Date of revision
 : 12/21/2015.

 Version : 4.2
 10/1

## Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

#### **National Fire Protection Association (U.S.A.)**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### **History**

**Date of printing** : 12/21/2015. **Date of issue/Date of** : 12/21/2015.

revision

**Date of previous issue** : 6/2/2015.

Version : 4.2

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

**References** : Not available.

Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

 Date of issue/Date of revision
 : 12/21/2015.

 Version : 4.2
 11/1