

SAFETY DATA SHEET

Section 1: Identification

Product Identification

Product Identifier: G20678, Utility Yellow
Recommended Use: Paint and coatings application.
Use Restrictions: Any that differs from the recommended use.

Company Identification

Company: Grabber Construction Products Inc.
Address: 5255 North 11000 West
Highland, Utah 84003
Phone: 1-801-492-3880
Website: www.grabberpro.com
Emergency: 1-800-255-3924
For most current SDS, please visit our website at: www.grabberpro.com/TechnicalDocuments/SDS

Section 2: Hazard(s) Identification

General Information

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.
Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.
Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure:
Inhalation.
Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms



GHS02 GHS04 GHS08

Signal word Hazard statements

Danger
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Suspected of causing cancer. Route of exposure: Inhalation.
May cause damage to organs through prolonged or repeated exposure.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves/protective clothing/eye protection/face protection.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Precautionary statements

Section 3: Composition Information

General Information

Chemical characterization: Mixtures
Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-89-8	VM&P Naphtha	15-25%
74-98-6	propane	15-25%
1317-65-3	Calcium Carbonate	≥15-<20%
106-97-8	n-butane	10-15%
64742-47-8	Mineral Spirits	1-5%
13463-67-7	titanium dioxide	1-5%

Section 4: First-Aid Measures

General Information

Indication of any immediate medical attention needed: No further relevant information available.

Routes of Exposure

After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	Rinse mouth with water. Do not induce vomiting.

Most Important Symptoms

Dizziness

Section 5: Fire-Fighting Measures

Suitable Extinguishing Media: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

Hazards during firefighting: Can form explosive gas-air mixtures.

Fire-fighting Protective Equipment: A respiratory protective device may be necessary.

Section 6: Accidental Release Measures

Personal Precautions

Protective equipment and emergency procedures: Use respiratory protective device against the effects of fumes/dust/aerosol.

Clean-Up Methods

Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

Section 7: Handling and Storage

Handling

Precautions for safe handling Use only in well-ventilated areas.

Storage

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
Store locked up.

Section 8: Exposure Controls/Personal Protection

Personal Protective Equipment

Eye Protection:	Tightly sealed goggles
Hand Protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Skin and Body Protection:	Wear long sleeve shirt/long pants and other clothing. . .
Respirator Protection:	A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long-term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
General Hygiene:	Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the eyes and skin. Do not eat or drink while working.

Exposure Limits

Components with limit values that require monitoring at the workplace:	
74-98-6 propane	
PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)
106-97-8 n-butane	
REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 1000 ppm (EX)

Section 9: Physical and Chemical Properties

Appearance:	Aerosol.
Odor:	Solvent.
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range:	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapor-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density:	Not determined.
Evaporation rate:	Not applicable.
Partition coefficient— n-octanol/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
Water:	22.3%

Section 10: Stability and Reactivity**Description**

Reactivity:	Stable at normal temperatures.
Chemical Stability:	Not fully evaluated.
Conditions to Avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Substances to Avoid:	No further relevant information available.
Hazardous Reactions	No dangerous reactions known.
Decomposition Products	No dangerous decomposition products known.

Section 11: Toxicological Information

LD/LC50 values that are relevant for classification:

13463-67-7 titanium dioxide

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rbt)
Inhalative	LD50/4 h	>6.82 mg/l (rat)

Sensitization: No sensitizing effects known.**Skin contact:** No irritant effect.**Eye contact:** No irritating effect.**Information on Toxicological Effects**

No data available.

Section 12: Ecological Information (non-mandatory)**General Information**

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.

Further Information

No further relevant information available.

Section 13: Disposal Considerations (non-mandatory)

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.**Recommended cleansing agent:** Water, if necessary with cleansing agents.**Section 14: Transport Information (non-mandatory)****General Information**

UN number:	UN1950
DOT:	UN1950
DOT:	Aerosols, flammable

ADR: 1950 Aerosols
 Transport hazard class(es):
 Class 2.1 Gases
 Marine pollutant No
 Special precautions for user: Warning: Gases
 EMS Number: F-D,S-U
 Packaging Group: --
 UN "Model Regulation": UN 1950 AEROSOLS, 2.1

Section 15: Regulatory Information

SARA Section 355 (extremely hazardous substances):	
None of the ingredients in this product are listed.	
SARA Section 313 (Specific toxic chemical listings):	
None of the ingredients in this product are listed.	
Toxic Substances Control Act (TSCA):	All hazardous ingredients are found on the inventory list of substances.
Canadian Domestic Substances List (DSL):	All ingredients are listed or exempted.
Consumer Product Safety Commission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemicals known to cause cancer:	
100-41-4	ethyl benzene
13463-67-7	titanium dioxide
Prop 65 chemicals known to cause birth defects or reproductive harm:	
None of the ingredients is listed.	
EPA:	
None of the ingredients is listed.	

Section 16: Other Information

Contact: Regulatory Affairs

Disclaimer

Disclaimer of Liability:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information and recommendations contained herein are believed to be true and accurate, but all statements or suggestions are made without any warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material, or the results to be obtained for the use thereof.

This Safety Data Sheet (SDS) is prepared by Grabber Construction Products Inc.