

## Submittal Sheet

Submittal Sheet #0309412A

### Bugle Streaker® Screws Made In USA (212A)

Product:	Item#	Description	Unit Pack
	768A6	6 x 2-in, Bugle Head, Streaker®, Phosphate, Bulk	3,500
	468A	6 x 1-5/8-in, Bugle Head, Streaker®, Phosphate, Bulk	5,000
	368A	6 x 1-1/4-in, Bugle Head, Streaker®, Phosphate, Bulk	8,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-18	1	Streaker	0.875	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-18	1.25	Streaker	1.125	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-18	1.125	Streaker	0.96	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.138	0.321	#6-18	1.625	Streaker	1.46	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.151	0.321	#7-16	2	Streaker	1.875	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.164	0.321	#8-15	2.5	Streaker	2.02	25 ga.	20 ga.	P
Streaker	Light Gauge Steel	Bugle Head	0.164	0.321	#8-15	3	Streaker	2.02	25 ga.	20 ga.	P

**NOTE:** Grabber screws with the item numbers ending in "A" are manufactured in the United States of America. Grabber American Made Screws are SPECIAL ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY.

**Application:** Attaches gypsum board or wood to wood or 25-20 ga. steel or wood. Standardbugle head.

- 1/2" and 5/8" single-layer gypsum board to steel studs and track
- 1/2" and multiple-layer gypsum board to steel studs and track
- Steel or wood cabinets through single-layer gypsum board to steel studs, 20 – 25 gauge
- OSB or plywood to 20 – 25 steel

**Description:** Bugle Head, #2 Phillips recess, 15 TPI, phosphate finish with 23+ single lead, extra sharp Streaker® point. Available in GrabberGard® Exterior finish and clear zinc silver finish. Meets ASTM 1002, ICBO 5280, and ISO 2002 certifications and standards


**Directions:** Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 4,000 rpm.

- Bugle Head is completely seated when the head is flush with the work surface.
- Overdriving may result in failure of the STREAKER® or strip-out of the worksurface.
- The STREAKER® must penetrate beyond the metal a minimum of threethread pitches.

**Certifications:** All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. The fasteners comply with ASTM C1002 performance requirements. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.



**Bugle Head Fine Thread Staker®**



SUBMITTAL APPROVALS:

.....  
JOB NAME

CONTRACTOR

DATE

**TRADEMARKS:**

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

**NOTICE:**

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

## Bugle Streaker® Screws Made In USA (212A)



### PRODUCT SPECIFICATIONS

<b>Fastener Classification</b>	Light Gauge Metal (20-25)
<b>Fastener Head</b>	Bugle
<b>Fastener Drive</b>	#2 Phillips
<b>Fastener Gauge</b>	#6, #8
<b>Fastener Point</b>	Streaker
<b>Fastener Package Type</b>	Packaged Screws
<b>Fastener Package Weight</b>	Bulk Box
<b>Fastener TPI</b>	15
<b>Fastener Coating</b>	Black/Gray Phosphate, Clear Zinc

### STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.