

Submittal Sheet

Submittal Sheet #0309042B

Flat Head LOX® Recess Subfloor Screws (282)

Product:	Item#	Description	Unit Pack
	C7125UL2	Underlayment, Flat Hd, Sharp Point, Black Phosphate, 7 x 1-1/4" - Collated	1000
	C8175L3YZ	Sub Floor, Waxed, Yellow Zinc, 8 x 1-3/4" - Collated	1000
	C8300L3YZ	Sub Floor, Waxed, Yellow Zinc, 8 x 3"	1000
	C8250L3YZ	Sub Floor, Waxed, Yellow Zinc, 8 x 2-1/2" - Collated	1000
	C8200L3YZ	Sub Floor, Waxed, Yellow Zinc, 8 x 2" - Collated	1000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Subfloor	Interior Wood	Flat Head	0.151	0.346	#7-8	1.25	Streaker	1	N/A	N/A	P
Subfloor	Interior Wood	Flat Head	0.164	0.354	#8-8	1.75	Streaker	1.625	N/A	N/A	YZ
Subfloor	Interior Wood	Flat Head	0.164	0.354	#8-8	2	Streaker	1.625	N/A	N/A	YZ
Subfloor	Interior Wood	Flat Head	0.164	0.354	#8-8	2.5	Streaker	2.125	N/A	N/A	YZ
Subfloor	Interior Wood	Flat Head	0.164	0.354	#8-8	3	Streaker	2.375	N/A	N/A	YZ

NOTE: YZ = Yellow Zinc
P = Phosphate

Application: LOX recess, screws for attaching plywood, OSB, and other subfloor materialsto wood joists.
• For use in interior wood to wood construction such attaching subfloor to joists.

Description: Professional wood to wood screw for attaching plywood, OSB and other subfloor materials for wood joists. The ribbed flat head design self-countersinks.
• LOX recess drive ensures positive engagement.
• Ribbed head ensures flush countersinking
• 8 TPI design provides increased holding power.

Directions: Use a standard screwgun with a depth-sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum andRPM range of 0 to 4,000.
• The Flat head is fully seated when the head is flush with the work surface.
• Overdriving may result in failure of the fastener or strip out of the work surface.
• For wood to wood connections, minimum penetration should be 7 diameters (e.g. 1-1/4" for #8 fastener)

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.

SUBMITTAL APPROVALS:

.....
JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Flat Head LOX® Recess Subfloor Screws (282)



PRODUCT SPECIFICATIONS

Fastener Classification	Interior Wood
Fastener Head	Flat
Fastener Drive	LOX #2, LOX #3
Fastener Gauge	#7, #8, #9
Fastener Point	Sharp
Fastener Package Type	Collated Screws (for automated feed systems)
Fastener Package Weight	Bulk Box
Fastener TPI	8, 15, 19
Fastener Coating	Black/Gray Phosphate, Yellow Zinc, Blue Zinc

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.