

Submittal Sheet

Submittal Sheet #157103-05

Flat Head Pilot Point Drivall® Screws (250)

Product:	Item#	Description	Unit Pack
	M175SDZJBW	8 x 1-3/4-in Flat Head, Pilot Point, Clear Zinc, Bulk	4,000
	CMG158SD	8 x 1-5/8-in, Flat Head, Pilot Point, Drivall®, GrabberGard®, Collated	1,000
	CM175SDZJBW	8 x 1-3/4-in, Flat Head, Pilot Point, Drivall®, Clear Zinc, Collated	1,000
	CM158SDZJBW	8 x 1-5/8-in, Flat Head, Pilot Point, Drivall®, Clear Zinc, Collated	1,000
	CM10178JBWRG	10 x 1-7/8-in, Flat Head, Pilot Point, Drivall®, GrabberGard®, Collated	1,000
	CM200SDZJBW	8 x 2-in, Flat Head, Pilot Point, Drivall®, Clear Zinc, Collated	1,000
	M10178SDZJBW	10 x 1-7/8-in, Flat Head, Pilot Point, Drivall®, Clear Zinc, Collated	3,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Drivall	Heavy Gauge Steel	Flat Head	0.164	0.354	#8-18	1.75	Pilot #3	1.125	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Flat Head	0.164	0.354	#8-18	1.625	Pilot #3	1.125	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Flat Head	0.164	0.354	#8-18	2	Pilot #3	1.125	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Flat Head	0.19	0.354	#10-18	1.875	Pilot #3	1.125	20 ga.	8 ga.	RG

NOTE: RG = GrabberGard® Exterior Grade Coating
YZ = Yellow Zinc Coating
CZ = Clear Zinc Coating

Application: Self drilling fastener for attaching 3/8" to 1" plywood or wood to 20-8 gauge steel

- Attaching 3/8" to 1" plywood to steel joists and frames, 20-8 gauge steel
- Wood to 20-8 gauge steel applications
- Dinsglass products to steel


Description: #2 LOX or Phillips recess drive, fine thread (18 TPI) with #3 point for 14- 16 ga.

- Superfast #3 drill point
- Flat head seats flush with fastening surface

Directions: Use a standard screwgun with a depth-sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and RPM range of 0 to 2,500.

- The Flat head is fully seated when the head is flush with the work surface.
- Overdriving may result in failure of the fastener or stripout of the work surface.
- The fastener must penetrate beyond the metal a minimum of three thread pitches.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.



Flat Head Pilot Point



SUBMITTAL APPROVALS:

.....
JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Flat Head Pilot Point Drivall® Screws (250)



PRODUCT SPECIFICATIONS

Fastener Classification	Heavy Gauge Metal (18 or thicker)
Fastener Head	Flat
Fastener Drive	#2 Phillips, LOX #2
Fastener Gauge	#6, #8, #10
Fastener Point	Drill, Pilot, #2 Drill, #3 Drill
Fastener Package Type	Packaged Screws, Collated Screws (for automated feed systems)
Fastener Package Weight	Bulk Box
Fastener TPI	16, 18, 20
Fastener Coating	Yellow Zinc, Clear Zinc, GrabberGard
Fastener Color	Gray, Yellow

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.