

Submittal Sheet

Submittal Sheet #0020031

Grabber Cement Board Drivall® Screws (268)

Product:	Item#	Description	Unit Pack
	GCB8125SD	8 x 1-1/4-in, Flat Wafer Head, Drill Point, Phillips, GrabberGard Gray, Bulk	5,000
	GCB10350SD	10 x 3-1/2-in, Flat Wafer Head, Drill Point, Phillips, GrabberGard Gray, Bulk	1,000
	GCB8158SD	8 x 1-5/8-in, Flat Wafer Head, Drill Point, Phillips, GrabberGard Gray, Bulk	4,000
	GCB8238SD	8 x 2-3/8-in, Flat Wafer Head, Drill Point, Phillips, GrabberGard Gray, Bulk	3,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Grabber	Cement Board	Wafer Head Ribbed	0.164	0.404	#8-18	1.25	Drill #3	1.25	20 ga.	12 ga.	RG
Grabber	Cement Board	Wafer Head Ribbed	0.164	0.404	#8-18	1.625	Drill #3	1.625	20 ga.	12 ga.	RG
Grabber	Cement Board	Wafer Head Ribbed	0.164	0.404	#8-18	2.25	Drill #3	2.25	20 ga.	12 ga.	RG

Application: Attaches cement board to steel. Features a .40 diameter head and GrabberGard® exterior coating.

- Three lengths available 8 x 1-1/4-in, 8 x 1-5/8-in and 8 x 2-3/8-in
- 1000 hr corrosion resistant finish per ASTM B117
- .40-in Wafer head and countersinking nibs.

Description: GRABBER cement board and high density sheathing screws have been specifically designed for use with cement board and high density exterior sheathing. These exterior grade corrosion resistant fasteners have a .40" (10.5mm) wafer head with nibs to facilitate seating and minimize strip out. GRABBER cement board screws are used for the attachment of these boards to steel from 20-12 gauge.

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and RPM range of 0 to 4,000. Install with head flush with board, no need to counter sink. Overdriving may result in failure of the fastener or strip-out of the work surface.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.

SUBMITTAL APPROVALS:

.....
JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Grabber Cement Board Drivall® Screws (268)



PRODUCT SPECIFICATIONS

Fastener Classification	Cement Board
Fastener Head	Thin Wafer
Fastener Drive	#2 Phillips, LOX #2
Fastener Gauge	#8, #10
Fastener Point	#3 Drill
Fastener Package Type	Packaged Screws, Collated Screws (for automated feed systems)
Fastener Package Weight	Mini Pack, 1lb Box, 5lb Box, Bulk Box
Fastener TPI	18
Fastener Coating	GrabberGard, GrabberGard Gray

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.