



GRABBER ALL WEATHER
SUBFLOOR ADHESIVE

PHYSICAL PROPERTIES (TYPICAL)	Type Synthetic elastomeric polymer	Weight/gallon 9.85 lbs.
	State Medium-viscosity mastic	Flashpoint Less than 0°F.
	Color Light tan	Freeze/thaw stability Will not freeze
	Solids 69%	Storage life 12 months in tightly closed containers at 75°F.
	Viscosity 110,000 cps	
	Calculated VOC: 362 g/L	

APPLICATION GUIDELINES	Application temperature 0°F. to 100°F.
	Service temperatures -20°F. to 120°F.
	Method of application Cartridge/caulking gun
	Coverage (maximum) Approximate length of bead according to bead diameter:

Container	1/8" bead	1/4" bead	3/8" bead
29 oz. Cartridge	355 ft.	89 ft.	39 ft.

Working time Approx. 20-30 minutes for 1/4" bead
Working surfaces Surfaces to be bonded should be clean and free from excessive oil, grease, water, dirt or any other material that may deter adhesion. Apply Grabber All Weather Subfloor Adhesive to each piece of furring, studs or floor joists to be covered. When bonding subfloors or wet, frozen and treated lumber, nail or screw each sheet as recommended by the American Plywood Association.
Cleanup Scrape off dried excess with a putty knife. Remove residue with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using solvents. NOTE: Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.

PRODUCT FEATURES	<ul style="list-style-type: none"> • Works extremely well in colder temperatures • Ideal for plywood, particleboard, OSB, and wet, frozen and ACA & CCA treated lumber • Fills gaps and irregularities between materials to provide a more solid backup surface • Exceeds the performance requirements of the American Plywood Association AFG-01 Specification and ASTM C557.
---------------------	--

LIMITATIONS	Grabber All Weather Subfloor Adhesive is not designed for continuous submersion or for use on polystyrene foams. For polystyrene foam, tub surrounds and most other plastics, we recommend Grabber Interior/Exterior Construction Adhesive.
-------------	---

ORDERING INFORMATION	Cat. No.	Size	Units per Package	Weight	Packages per Pallet
	GSAF	29 oz. Cartridge	12	30	38

CAUTION STATEMENT	<p>DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. Contains hexane and toluene. Keep away from heat, sparks and flame. Use only with positive cross-ventilation. Avoid breathing vapors. Do not swallow. Do not allow eye contact or prolonged skin contact. Uncured product can cause eye or skin irritation. Prolonged or repeated overexposure to solvent in uncured product can cause central nervous system, peripheral nervous system, eye, skin, liver, kidney or respiratory system effects. First Aid: If dizziness or other adverse effects are experienced, move to fresh air; call physician if discomfort persists. If eye contact occurs, flush eyes with water for 15 minutes; contact physician immediately. If swallowed, do not induce vomiting; contact physician immediately. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Material Safety Data Sheet. KEEP OUT OF THE REACH OF CHILDREN.</p> <p>WARNING: This product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.</p>
----------------------	--

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.