

Submittal Sheet

Submittal Sheet #03040910-H

Hex Head Fine Thread Streaker® Screws (218)

Product:	Item#	Description	Unit Pack
	25Z	8 x 9/16-in, Hex Head, Fine Thread, STREAKER®, Clear Zinc, Bulk	10,000
	25	8 x 9/16-in, Hex Head, Fine Thread, STREAKER®, Black Phosphate, Bulk	10,000
	25100Z	8 x 9/16-in, Hex Head, Fine Thread, STREAKER®, Clear Zinc, Bulk	7,500
	25150Z	8 x 1-1/2-in, Hex Head, Fine Thread, STREAKER®, Clear Zinc, Bulk	5,000
	25SZ	8 x 9/16-in, Hex Head, Fine Thread, STREAKER®, Clear Zinc, Bulk	10,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Streaker	Light Gauge Steel	Hex Washer Head	0.164	0.335	#8-15	0.5	Streaker	0.5	25 ga.	20 ga.	Z
Streaker	Light Gauge Steel	Hex Washer Head	0.164	0.335	#8-15	0.5625	Streaker	0.5625	25 ga.	20 ga.	Z

Application: High-torque hex washer head for fast framing and sheet metal work in 25-20 ga. Use 1/4-in nut setter.


Description: A fine thread screw for metal-to-metal framing applications. 15 threads per inch. High torque hex head, which can be easily removed when necessary. Super sharp, 23° STREAKER® point, designed to penetrate steel quickly and easily.

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and RPM range of 0 to 4,000. The Hex head is fully seated when the head is flush with the work surface. Overdriving may result in failure of the fastener or stripout of the work surface. The fastener must penetrate beyond the metal a minimum of three thread pitches.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. The fasteners comply with ASTM C1513 specifications and requirements. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.



Hex Head Fine Thread Streaker®



SUBMITTAL APPROVALS:

.....
JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Hex Head Fine Thread Streaker® Screws (218)



PRODUCT SPECIFICATIONS

Socket	5/16"
Socket	5/16"
Fastener Classification	Light Gauge Metal, Light Gauge Metal (20-25)
Fastener Head	Hex
Fastener Drive	Hex
Fastener Gauge	#8, #10
Fastener Point	Streaker
Fastener Package Type	Packaged Screws
Fastener Package Weight	1lb Box, 5 Pound, Bulk Box
Fastener TPI	15
Fastener Coating	Black/Gray Phosphate, Blue Zinc, Clear Zinc

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.