

## Submittal Sheet

Submittal Sheet #Product 240S

### Scavenger® Head Drivall® Screws (240S)

Product:	Item#	Description	Unit Pack
	C30SZ	8 x 2-3/8-in, Scavenger® Head, Drivall®, Clear Zinc, Collated	1,000
	13SZ	6 x 1-in, Scavenger® Head, Drill Point, Clear Zinc, Bulk	10,000
	13S	6 x 1-in, Scavenger® Head, Drill Point, Phosphate, Bulk	10,000
	30LSZ	8 x 3-in, Scavenger® Head, Drill Point, Clear Zinc, Bulk	2,000
	30MSZ	8 x 2-5/8-in, Scavenger® Head, Drivall®, Clear Zinc, Bulk	2,000
	30SSZ	8 x 2-3/8-in, Scavenger® Head, Drill Point, Clear Zinc, Bulk	3,000
	16SZ	6 x 1-7/8-in, Scavenger® Head, Drill Point, Clear Zinc, Bulk	4,000
	15SZ	6 x 1-5/8-in, Scavenger® Head, Drill Point, Clear Zinc, Bulk	5,000
	14SZ	6 x 1-1/4-in, Scavenger® Head, Drill Point, Clear Zinc, Bulk	8,000
	135SZ	6 x 1-1/8-in, Scavenger® Head, Drill Point, Clear Zinc, Bulk	10,000
	14S	6 x 1-1/4-in, Scavenger® Head, Drill Point, Phosphate, Bulk	8,000
	135S	6 x 1-1/8-in, Scavenger® Head, Drill Point, Phosphate, Bulk	10,000
	15S	6 x 1-5/8-in, Scavenger® Head, Drill Point, Phosphate, Bulk	5,000
	16S	6 x 1-7/8-in, Scavenger® Head, Drill Point, Phosphate, Bulk	4,000
	30SS	8 x 2-3/8-in, Scavenger® Head, Drill Point, Phosphate, Bulk	3,000
	30MS	8 x 2-5/8-in, Scavenger® Head, Drill Point, Phosphate, Bulk	2,000
	30LS	8 x 3-in, Scavenger® Head, Drill Point, Phosphate, Bulk	2,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Scavenger	Heavy Gauge Steel	Scavenger Head	0.138	0.321	#6-20	1	Drill #3	0.75	20 ga.	12 ga.	P, Z
Scavenger	Heavy Gauge Steel	Scavenger Head	0.138	0.321	#6-20	1.25	Drill #3	1	20 ga.	12 ga.	P, Z
Scavenger	Heavy Gauge Steel	Scavenger Head	0.138	0.321	#6-20	1.125	Drill #3	0.875	20 ga.	12 ga.	P, Z
Scavenger	Heavy Gauge Steel	Scavenger Head	0.138	0.321	#6-20	1.625	Drill #3	1.375	20 ga.	12 ga.	P, Z
Scavenger	Heavy Gauge Steel	Scavenger Head	0.138	0.321	#6-20	1.875	Drill #3	1.625	20 ga.	12 ga.	P, Z
Scavenger	Heavy Gauge Steel	Scavenger Head	0.164	0.321	#8-18	2.375	Drill #3	1.625	20 ga.	12 ga.	P, Z
Scavenger	Heavy Gauge Steel	Scavenger Head	0.164	0.321	#8-18	2.625	Drill #3	1.625	20 ga.	12 ga.	P, Z
Scavenger	Heavy Gauge Steel	Scavenger Head	0.164	0.321	#8-18	3	Drill #3	1.875	20 ga.	12 ga.	P, Z

**NOTE:** Z = Clear Zinc  
RG = GrabberGard® Exterior Grade Coating

**Application:** Attaches gypsum, insulation board, wood, etc. to metal studs 20-12 ga. Unique Scavenger® head helps reduce paper burrs.

- Gypsum board to 20-12 gauge steel studs and track
- Insulation to steel, 20-12 gauge

---

**Description:**

Self drilling screws for attaching gypsum board to 14 to 20 gauge steel. Features a unique double-bugle or Scavenger® head design that reduces paper burrs in drywall attachment.

- Self tapping drill point is designed for penetration into 20-12 gauge steel
  - #2 Phillips recess drive
  - Scavenger® head will seat fast and easily and create a flush surface finish
  - Unique head configuration helps eliminate paper burrs and aids proper seating of fasteners
- 

**Directions:**

Use a standard screwgun with a depth-sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and RPM range of 0 to 2,500.

- The Scavenger head is fully seated when the head is flush with the work surface.
  - Overdriving may result in failure of the fastener or stripout of the work surface.
  - The fastener must penetrate beyond the metal a minimum of three thread pitches.
- 


**Certifications:**

All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. The fasteners comply with the performance requirements of ASTM C954. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.

---



Scavenger® Head Coarse Thread



SUBMITTAL APPROVALS:

.....  
JOB NAME

CONTRACTOR

DATE

**TRADEMARKS:**

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

**NOTICE:**

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

## Scavenger® Head Drivall® Screws (240S)



### PRODUCT SPECIFICATIONS

<b>Fastener Classification</b>	Heavy Gauge Metal, Heavy Gauge Metal (18 or thicker)
<b>Fastener Head</b>	Scavenger, Flat
<b>Fastener Drive</b>	#2 Phillips
<b>Fastener Gauge</b>	#6, #7, #8
<b>Fastener Point</b>	Drill, Drill, S-12
<b>Fastener Package Type</b>	Packaged Screws, Collated Screws (for automated feed systems)
<b>Fastener Package Weight</b>	Mini Pack, 1lb Box, 5 Pound, 5lb Box, Bulk Box
<b>Fastener TPI</b>	16, 18, 19, 20
<b>Fastener Coating</b>	Black/Gray Phosphate, Gray Phosphate, Clear Zinc, GrabberGard

### STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.