

Submittal Sheet

Submittal Sheet #0309042-S

Scavenger® Head Fine Thread Streaker® Screws (210)

Product:	Item#	Description	Unit Pack
	168S	6 x 1-in, SCAVENGER® Head, Fine Thread, Bulk	10,000
	368SV	6 x 1-1/4-in, SCAVENGER® Head, Vector™ Point, Fine Thread, Bulk	8,000
	368S	6 x 1-1/4-in, SCAVENGER® Head, Fine Thread, Bulk	8,000
	268S	6 x 1-1/8-in, SCAVENGER® Head, Fine Thread, Bulk	10,000
	468S	6 x 1-5/8-in, SCAVENGER® Head, Fine Thread, Bulk	5,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Scavenger	Light Gauge Steel	Scavenger Head	0.138	0.325	#6-15	1	Streaker	0.875	25 ga.	20 ga.	P
Scavenger	Light Gauge Steel	Scavenger Head	0.138	0.325	#6-15	1.25	Streaker	1.125	25 ga.	20 ga.	P
Scavenger	Light Gauge Steel	Scavenger Head	0.138	0.325	#6-15	1.125	Streaker	0.96	25 ga.	20 ga.	P
Scavenger	Light Gauge Steel	Scavenger Head	0.138	0.325	#6-15	1.625	Streaker	1.46	25 ga.	20 ga.	P

NOTE: BHS = Scavenger Head
PH = Phosphate Coating
SP = Streaker Point

Application: Attaches gypsum board to 25-20 ga. steel. Unique Scavenger® head helps reduce paper burrs.

Description: Unique Scavenger® head configuration helps eliminate paper burrs and aids proper seating of fasteners. A fine thread screw for general interior applications 15 threads per inch. Super sharp, 23° STREAKER® point, designed to penetrate steel quickly and easily. #2 Phillips recess drive

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and RPM range of 0 to 4,000. The SCAVENGER® head is fully seated when the head is flush with the work surface. Overdriving may result in failure of fastener or strip out of the work surface. The fastener must penetrate beyond the metal three full thread pitches.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. The fasteners comply with ASTM C1002 performance requirements. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.

SUBMITTAL APPROVALS:

.....
JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Scavenger® Head Fine Thread Streaker® Screws (210)



PRODUCT SPECIFICATIONS

Fastener Classification	Light Gauge Metal (20-25)
Fastener Head	Scavenger
Fastener Drive	#2 Phillips
Fastener Gauge	#6
Fastener Point	Streaker, Vector™
Fastener Package Type	Packaged Screws
Fastener Package Weight	Mini Pack, 1lb Box, 5 Pound, Bulk Box
Fastener TPI	15
Fastener Coating	Black/Gray Phosphate, Gray Phosphate

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.