



SCORPION BRAND

INNOVATION SINCE 1975

Submittal Sheet #SCORPHT1

PRODUCT:

HT118	Bulge	6 x 1 1/8"
HT114	Bulge	6 x 1 1/4"
HT158	Bulge	6 x 1 5/8"
HT200	Bulge	6 x 2

Application: The Bugle Head, coarse thread sharp point is used for the attachment of drywall, wood and composite or core board to light (20-25) gauge steel stud or light gauge metal.

Description: Bugle Head, #2 Phillips Recess Drive, 8 TPI, Black Phosphorus Finish with 23 1/4 single lead, point. Available in NanoGard® Exterior finish and clear zinc silver finish.

Meets ASTM C1002, and ISO 9002 certifications and standards

Directions: Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 4,000 rpm. Bugle Head is completely seated when the head is flush with the work surface. Overdriving may result in failure of the fastener, the metal the fastener is attaching to or stripping of the head recess. Penetration of three thread pitches beyond the penetrated metal is minimum.



SCORPION BRAND
INNOVATION SINCE 1975

Submittal Sheet #SCORPHT1

JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.



SCORPION BRAND

INNOVATION SINCE 1975

Submittal Sheet #SCORPHT1

Coarse Thread




Bugle Head



Gimlet Point



#2 Phillips Drive



Features:

Coarse thread bugle head screws for drywall and general interior applications. Sharp 25° Point means quick and easy penetration into light gauge metal or wood.

PRODUCT SPECIFICATIONS

Fastener Classification Type "W" C1002
 Fastener Head Bugle
 Fastener Drive #2 Phillips
 Fastener Gauge #6, #7, #8, #10
 Fastener Point Self Piercing
 Fastener Package Type Packaged Screws
 Fastener Package Weight 1lb Box, 5 Pound, Bulk Box

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Black/Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust

All Scorpion screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C 1002, and are approved for use by the Uniform Building Code, International Residential Code, and International Building Code.
 ©2014 Scorpion® are registered names or trademarks by Grabber Construction Products Inc.