

Submittal Sheet #SCORPSP1

PRODUCT:	Head:	Head dia.:	Size:
SP100	Bugle	0.323"	6 x 1"
SP118	Bugle	0.323"	6 x 1 1/8"
SP114	Bugle	0.323"	6 x 1 1/4"
SP158	Bugle	0.323"	6 x 1 5/8"
SP200	Bugle	0.323"	6 x 2

Application: The Bugle Head, fine thread sharp point is used for the attachment of drywall, wood and composite or core board to light (20-25) gauge steel stud or light gauge metal.

Description: Bugle Head, #2 Phillips Recess Drive, 17 TPI, Black Phosphorus Finish with shapr single lead, point. Available in NanoGard® Exterior finish and clear zinc finish.

Meets ASTM C1002, and ISO 9001 certifications and standards

Directions: Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 4,000 rpm. Bugle Head is completely seated when the head is flush with the work surface. Overdriving may result in failure of the fastener, the metal the fastener is attaching to or stripping of the head recess. Penetration of three thread pitches beyond the penetrated metal is minimum.

Phone: (800)-233-0461

Fax: (800)-750-1063



Submittal Sheet #SCORPSP1

JOB NAME	
CONTRACTOR	DATE

TRADEMARKS:


NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.



Submittal Sheet #SCORPSP1

Fine Thread



Features:

Fine thread bugle head screws for drywall and general interior applications. Sharp Point means quick and easy penetration into light gauge metal or wood.

PRODUCT SPECIFICATIONS

Fastener Classification Light Gauge Metal

Fastener Head Bugle (head dia. 8.2 mm [0.323 in])

Fastener Drive #2 Phillips

Fastener Gauge #6, #7, #8, #10

Fastener Point Self Piercing
Fastener Package Type Packaged Screws

Fastener Package Weight 11b Box, 5 Pound, Bulk Box

STANDARD CORROSION TEST RESULTS

Finish Test Standard/Protocol Results
Black/Gray Phosphate Salt Spray Results ASTM B117 24 hou

Black/Gray Phosphate Salt Spray Results
Yellow Zinc Salt Spray Results
Clear Zinc Salt Spray Results
ASTM B117 24 hours, no red rust
ASTM B117 24 hours, no red rust
ASTM B117 12 hours, no red rust

All Scorpion screw products are manufactured in facilities that are ISO 9001 certified and approved. The fasteners comply with ASTM C1002. ©2014 Scorpion® are registered names or trademarks by Grabber Construction Products Inc.