



GrabberGard Fasteners for ACQ – Pressure Treated Lumber

Use stainless steel when maximum corrosion resistance is required.

Use hot dipped galvanized when lesser corrosion resistance is required.

PRODUCT SPECIFICATIONS

Fastener Classification	Exterior/Interior Wood
Fastener Head	Flat
Fastener Drive	LOX 2
Fastener Gauge	#8 - #10
Fastener Point	QuickGrab Type 17
Fastener Package Type	Bulk, 5lb, 1lb and mini pack

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
GrabberGard	Salt Spray Results	ASTM B117	1,500 hours no red rust GrabberGard

All GRABBER® screw products are manufactured in facilities that are ISO 9002 certified and approved. The fasteners comply with ANSI/ASME B18.6.1, as referenced in ICC ES report are approved for use in structures governed by the International Building Code 2009, 2012, 2015, International Residential Building Code 2009, 2012, 2015.

Salt Spray Results ASTM B117 1500 hours, no red rust:

GrabberGard® metal finish is a high-grade proprietary metal surface processing technology that prevents corrosion. It is a duplex coating constituting a zinc substrate and organic polymer topcoat. The distinguishing feature of GrabberGard® is the joining and encapsulation the substrate with the fused organic surface coating. These layers are bonded together through thermal fusion, and this unique method of combining layers results in a combination of the coating films. Suitable for use in non coastal areas with all pressure treated lumbers including ACQ.

GRABBERGARD®, and SCAVENGER II ® are registered names or trademarks by Grabber Construction