

# Specification Sheet

## Acrylitex Smooth Wall PF4505-01



**Manufacturer:** Acrylic Technologies, Inc.  
8914 NE Alderwood Rd. Portland, OR 97230  
Phone: 503.282.2591

**Product Description:** Acrylitex Smooth Wall is a PVA product applied in a production spray application to create a smooth wall finish. It takes a level 4 finish to level 5 without the need to putty coat by hand. Eliminates the intensive labor necessary with the traditional method and can be sanded. This product has exceptional hide and a self-leveling characteristic.

**Coverage:** Approximately 85-110 square feet per gallon. Coverage rates will vary with mil thickness, applicator technique and type of spray tip (amount of fallout).

**Recommended Mil Rate:** Apply 15 wet mils per application. See Applicator Tips.

**Packaging:** Available in 5 gallon and 55 gallon containers and 275 gallon totes.

**Colors:** Available in one color – White.

### **Preparation for Substrates of Gypsum and Concrete:**

1. Surfaces must be clean, dry, sound and properly cured.
2. Surfaces must be free of sanding dust, dirt, oil, grease, mildew, fungus, efflorescence, loose paint or other contaminants.
3. Surfaces must be free of chalking, blistering, peeling, cracking and delaminating
4. Surface must be completely dry before application.

**Application Equipment:** Apply Acrylitex Smooth Wall with an airless that sprays at least 1 gallon per minute. Respirator not required but recommended. Clean tools, equipment and skin with soapy water and rinse.

**Application:** Product is bucket ready. No thinning necessary.

Acrylitex Smooth Wall is designed for use as an undercoating for finish paint on interior walls and ceilings. Our liability is expressly limited to the replacement of defective product.

For additional information, contact Manufacturer.