

## PRODUCT SUBMITTAL

**Submitted to:**

Project:

Date of Submittal:

**Submitted by, Contact name:**

Company:

Address:

Phone:

Email:

Approved

Approved as Noted

Not Approved

Comments:

By:

Date:

---

List of items from Table A submitted for the project:

--

## Product Family: PSH - Self-Piercing Scavenger Head Hi-Lo Thread

**TABLE A**

Item Number	Screw Size (#)	Length (in.)	Head Style	Head Diameter (in.)	TPI	Point Size/Style	Coating	Maximum Total Drilling Thickness (in.)	Drive Type	Bulk Quantity
168SHL	6	1-in	Scavenger®	0.325	18 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	10,000
268SHL	6	1-1/8-in	Scavenger®	0.325	18 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	10,000
C268SHL	6	1-1/8-in	Scavenger®	0.325	18 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	1,000
368SHL	6	1-1/4-in	Scavenger®	0.325	18 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	8,000
C368SHL	6	1-1/4-in	Scavenger®	0.325	18 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	1,000
468SHL	6	1-5/8-in	Scavenger®	0.325	18 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	5,000
C468SHL	6	1-5/8-in	Scavenger®	0.325	18 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	1,000
768SHL	7	2-in	Scavenger®	0.325	16 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	3,500
868SHL	7	2-1/4-in	Scavenger®	0.325	16 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	3,000
968SHL	8	2-1/2-in	Scavenger®	0.325	15 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	2,500
1168SHL	8	3-in	Scavenger®	0.325	15 Hi-Lo	Streaker	Phosphate	0.033	#2 Phillips	2,000

Grabber screws manufactured in America are available as SPECIAL-ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY. For identification purposes, an "A" will be added to the end of the item number and "Made in America" will be printed on the label.

Prefixes: X = 1-lb, VB = 5-lb, BP = Blister Pack, C = Collated

Description: Scavenger head Streaker point screw used in light-gauge (see TABLE A - Maximum Total Drilling Thickness) steel or wood applications. Self-tapping Streaker point is designed for penetration into light-gauge steel, or wood.

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance - Sizes #6 - #8, up to 4,000 RPM. For gypsum board, the Scavenger head is fully seated when the screw is below the surface of the wallboard in accordance with Section 7.2.2 of ASTM C1002. Overdriving may result in failure of the fastener. The fastener must penetrate beyond the metal a minimum of three full threads.

Corrosion: For Corrosion Resistance Testing Results, see TABLE B.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9001 certified. PSH fasteners are used for gypsum board to light-gauge steel and gypsum board to wood applications and comply with ASTM C1002 and ASTM C1513 requirements.

## PSH - Self-Piercing Scavenger Head Hi-Lo Thread



**TABLE B**

CORROSION RESISTANCE TESTING RESULTS			
Finish	Test	Standard/Protocol	Results (minimum)
Phosphate	Salt Spray	ASTM B117	24 hours, no red rust

NOTE: Salt Spray Testing (SST) results are not intended to predict corrosion resistance in real-world environments. The ASTM B117 standard for SST is recognized industry-wide as an effective tool to compare different metals and different metal coatings in a tightly controlled highly corrosive environment for specific periods of time. For more information about corrosion resistance, see the *Grabber Guide to Corrosion Resistance for Fasteners*.

Grabber's approved mills keep tight control over all production standards and processes. Grabber's mills are ISO 9001 ensuring Grabber fasteners meet or exceed the highest industry standards.

### TRADEMARKS:

The following registered trademarks used herein are owned by Grabber Construction Products, Inc.:

GRABBER®  
Scavenger®

### NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.