

## PRODUCT SUBMITTAL

**Submitted to:**

Project:

Date of Submittal:

**Submitted by, Contact name:**

Company:

Address:

Phone:

Email:

Approved

Approved as Noted

Not Approved

Comments:

By:

Date:

---

List of items from Table A submitted for the project:

--

## Product Family - S-PTF - SCORPION-Self-Piercing Trim Head Fine Thread

**TABLE A**

Item Number	Screw Size (#)	Length (in.)	Head Style	Head Diameter (in.)	TPI	Point Size/Style	Coating	Maximum Total Drilling Thickness	Drive Type	Bulk Quantity
SPTR158	6	1-5/8-in.	Trim	0.219-in.	15	STREAKER®	Phosphate	0.033-in.	#1 Square	5,000
SPTR214	6	2-1/4-in.	Trim	0.219-in.	15	STREAKER®	Phosphate	0.033-in.	#1 Square	3,000
SPTR300	8	3-in.	Trim	0.219-in.	15	STREAKER®	Phosphate	0.033-in.	#1 Square	2,000

Item Number Code: PP = 1-lb, FP = 5-lb, CP = Count Pack,

Description: Self-piercing trim head fine thread screws for wood to wood, or wood to light-gauge metal applications.

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance - Size #6 to #8, up to 4,000 RPM. Overdriving may result in failure of the fastener.

Corrosion: For corrosion resistance results, see Table B.

## S-PTF - SCORPION-Self-Piercing Trim Head Fine Thread



**TABLE B**

CORROSION RESISTANCE TESTING RESULTS			
Finish	Test	Standard/Protocol	Results (minimum)
Phosphate	Salt Spray	ASTM B117	24 hours, no red rust

NOTE: Salt Spray Testing (SST) results are not intended to predict corrosion resistance in real-world environments. The ASTM B117 standard for SST is recognized industry-wide as an effective tool to compare different metals and different metal coatings in a tightly controlled highly corrosive environment for specific periods of time. For more information about corrosion resistance, see the *Grabber Guide to Corrosion Resistance for Fasteners*.

### TRADEMARKS:

The following trademarks used herein are owned by Grabber Construction Products, Inc.:

GRABBER®  
SCORPION®

### NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.